

AUTORIZED RELEASE CERTIFICATE

FAA FORM 8130-3, AIRWORTHINESS APPROVAL TAG

1. Approving Civil Aviation Authority/Country:
FAA/UNITED STATES

3. Form Tracking Number:
5954103 EI 1.000

4. Organization Name and Address:

**Hamilton Sundstrand Aerospace
Division of Hamilton Sundstrand Corporation
4747 Harrison Avenue Rockford, IL 61108-7929**


5. Work Order/Contract/Invoice Number:
**5954103 EI
1000259213**

PQ2016CE

6. Item:	7. Description:	8. Part Number:	9. Quantity:	10. Serial Number:	11. Status/Work:
1	ROLLER, BEARING ELEMENT	4004C5-5-10	15	N/A	NEW

12. Remarks: **EXPORT AIRWORTHINESS APPROVAL**
 This ROLLER, BEARING ELEMENT is a subcomponent of an FAA PMA article.
 No Special import requirements for UNITED ARAB EMIRATES stated at time of issuance.

13a. Certifies the items identified above were manufactured in conformity to:
 Approved design data and are in a condition for safe operation.
 Non-Approved design data specified in Block 12.

13b. Authorized Signature:  SCOTT GREENE	13c. Approval/Authorization No.: ODA810310NE	14c. Approval/Certificate No.
13d. Name (Typed or Printed): SCOTT GREENE	13e. Date (dd/mm/yyyy): 13 Mar 2014	14e. Date (dd/mm/yyyy)

User/Installer Responsibilities

It is important to understand that the existence of this document alone does not automatically constitute authority to install the aircraft engine/propeller/article.

Where the user/installer performs work in accordance with the national regulations of an airworthiness authority different than the airworthiness authority of the country specified in Block 1, it is essential that the user/installer ensures that his/her airworthiness authority accepts aircraft engine(s)/propeller(s)/article(s) from the airworthiness authority of the country specified in Block 1.

Statements in Block 13a and 14a do not constitute installation certification. In all cases aircraft maintenance records must contain an installation certification issued in accordance with the national regulations by the user/installer before the aircraft may be flown.